

PRESSALIT.

| Product | VALUE support arm, height adjustable | |
|-------------------|---|--|
| Item number | R1110000 | |
| | VVS:615722405 | |
| | NRF:6191643 | |
| | RSK:7972412 | |
| | EAN:5708590176420 | |
| | HMI: 25413 | |
| | NBS:N13:436 | |
| | FDA:ILS/D135866 | |
| Colour | White | |
| Δdiustahility | The ergonomic design gives a secure and comfortable grip as well as a good sense of where the support arm ends. Incl. fixing bolts for brick wall. Plugs depend on wall type and must be ordered separately. VALUE support arm, wall-mounted, foldable, height adjustable 150 mm, projection 865 mm. The ergonomic design gives a secure and comfortable grip as well as a good sense of where the support arm ends. Materials: Rilsan-coated steel, diecast aluminium, plastic. Incl. fixing bolts for brick wall. Plugs depend on wall type and must be ordered separately. Height adjustable | |
| Adjustability | Height adjustable | |
| Adjustment height | 150 mm | |
| Product capacity | Maximum load: 120 kg. When the support arm is loaded with 120 kg, each wall fastener is loaded with 86 kg | |
| Materials | The support arm is manufactured from steel with a Rilsan coating, which is comfortable to the touch, easy to clean, and protects the metal against corrosion. The end caps are manufactured from nylon (PA). | |



PRESSALIT.

| Product Item number | VALUE support arm, height adjustable R1110000 |
|------------------------|---|
| Ergonomy | Provides firm support when you are sitting, standing, or transferring to and from a toilet. |
| | Good, broad support surface for the hand and arm. The rounded form gives a firm and comfortable grip. |
| Features | The support arm can fold up when not in use or to make more space. |
| | Height adjustable 150 mm. |
| Warranty | Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date. |



PRESSALIT.®

| Product | VALUE support arm, height adjustable | |
|---------------------------|---|--|
| Item number | R1110000 | |
| Cleaning | VALUE support arms. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use corrosive or abrasive cleaners as it may result in the surface being damaged. For surface disinfection, chlorine-based disinfectants may be used according to the product specification and safety precautions for these products. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium | |
| | Tvättsprit 70% WipeClean UniversalCleaning Chrolorine Disinfection Wipes Klorilli (Kiilto Clean) NON-DISINFECTANTS: Suma Star free D1 Taski 100 | |
| | Taski 200 Milizid Citro The product must be wiped down with a soft rag wrung out in clear water immediate after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate. | |
| Declaration of conformity | CE MDR This product is in compliance with all relevant requirements of: - Regulatio (EU) 2017/745 on medical devices. | |



PRESSALIT.

VALUE support arm, height adjustable

Item number

R1110000

Installation in different wall types


| a. V. O. | ا · ا |
|---------------|--------------|
| ο | , a. |
| 2 2 . | B. 7. C |
| O. O. D. | |
|] • d • D • [| (, , , , ,) |

Concrete >B25

V8592 - 5 countersunk screws Ø10 x 80, with white screw covers are included.

Plugs to be ordered separately.






Solid Brick >= Mz12

V8592 - 5 countersunk screws \emptyset 10 x 80, with white screw covers are included.

Plugs to be ordered separately.





Solid Sand Lime Brick >= Hlz12

V8592 - 5 countersunk screws Ø10 x 80, with white screw covers are included.

Plugs to be ordered separately.






Aerated Concrete P4

V8592 - 5 countersunk screws Ø10 x 80, with white screw covers are included.

Plugs to be ordered separately.





Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8592 - 5 countersunk screws Ø10 x 80, with white screw covers are included.

Plugs to be ordered separately.





PRESSALIT®

| Product Item number | VALUE support arm, height adjustable R1110000 | |
|------------------------|---|---|
| | Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (5 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar. | |
| | Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (5 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar. | |
| | Drywall (2 x 12,5 mm) water-resistant | |
| | Mounting in this wall type is not recommended - risk of fatal injury to persons and walls. | ! |

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com