
| | |
|---|---|
| **Product** | PLUS anglehandrail section 400 x 154 mm, incl. wall rosette |
| **Item number** | RT341000 |
| | VVS:777569410<br>NRF:6311272<br>EAN:5708590146676<br>NBS:N13:436 |
| **Colour** | White |
| **Product description** | PLUS angle hand rail tube, left, 90° angle with one wall rosette and connecting unit male joint.<br>400 x 154 mm, diameter 33 mm.<br>Requires other hand rail elements for installation.<br>*Please enquire for special hand rail solutions.*<br>Please note that RT360 PLUS hand rail wall mounting with strap must always be installed at all joints of tubes or every 1200 mm.<br>Excl. mounting kit.<br>See Technical datasheet (pdf) for information on fixings suitable for various wall types.<br><br>PLUS angle hand rail tube, left, 90° angle with one wall rosette and connecting unit male joint.<br>400 x 154 mm, diameter 33 mm.<br>Requires other hand rail elements for installation.<br>*Please enquire for special hand rail solutions.*<br>Please note that RT360 PLUS hand rail wall mounting with strap must always be installed at all joints of tubes or every 1200 mm.<br>Materials: Powder-coated aluminium and plastics.<br>Excl. mounting kit. |
| **Product capacity** | Maximum load: With a span up to 1000 mm: 210 kg<br>With a span up to 1300 mm: 150 kg. |
| **Materials** | Basic material: Aluminium<br><br>Surface material: Polyester lacquer<br><br>Cover cap: Cycoloy plastic |
| **Ergonomy** | The 33 mm diameter enables the rail to be held comfortably and firmly. The projection of 50 mm from the wall makes it easy to take hold of the rail. |




| | |
|---|---|
| **Product** | PLUS anglehandrail section 400 x 154 mm, incl. wall rosette |
| **Item number** | RT341000 |
| **Warranty** | Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date. |
| **Cleaning** | The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based or corrosive cleaners as it may result in the surface being damaged. |

PRESSALIT®


| | |
|---|---|
| **Product** | PLUS anglehandrail section 400 x 154 mm, incl. wall rosette |
| **Item number** | RT341000 |


# Installation in different wall types



**Concrete >B25**


V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.






**Solid Brick >= Mz12**


V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.






**Solid Sand Lime Brick >= Hlz12**


V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.






**Aerated Concrete P4**


V8665 - Mounting kit, 4 bolts M5 x 50 - plugs FTP K 6.
To be ordered separately.






**Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood**

V8615 - Mounting kit, 4 screws Ø5 x 50 - plugs SX8. NB!
Plugs are not needed.
To be ordered separately.





| | |
|---|---|
| **Product** | PLUS anglehandrail section 400 x 154 mm, incl. wall rosette |
| **Item number** | RT341000 |



**Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood**


Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.






**Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)**

Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.





**Drywall (2 x 12,5 mm) water-resistant**

Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.





Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com