




# PRESSALIT®

<b>Product</b> <b>Item number</b>	PLUS shower seat 310, fixed height R7310000
<b>Colour</b>	VVS:777533000 NRF:6311141 EAN:5708590309453 HMI: 71807 NBS:N13:448 FDA:INN/D135865 White
<b>Product description</b>	 <p>PLUS shower seat 310. For fixed mounting. The seat is foldable.  Materials: Comfortable polyurethane foam over a plywood core, fitted to an aluminium profile.  Incl. mounting kit for brick wall.</p> <p>PLUS shower seat 310. For fixed mounting. The seat is foldable.  Materials: Comfortable polyurethane foam over a plywood core, fitted to an aluminium profile.  Incl. mounting kit for brick wall.</p>
<b>Adjustability</b> <b>Product capacity</b>	Fixed mounting  Maximum user mass: 200 kg. When the seat is loaded with 200 kg, each wall fastener is loaded with 113 kg.  <i>The seat has been tested statically with safety factor 1.5, which is a requirement according to the applied assistive products standards.</i>
<b>Materials</b>  <b>Ergonomy</b>  <b>Features</b>	<p>The shower seat is made of polyurethane (PU) foam with a plywood core and this is covered with an in-mould coated surface that is protected using a clear PU lacquer. Internal components and fasteners are primarily made of stainless steel. The hinge barrel is capped with ABS.</p> <p>Ergonomically designed seat - contact surface are 310 x 365 mm. Soft and slip-resistant material that has a warm feel.</p> <p>The seat can fold up when not in use or to maximise floor space.</p>
<b>Warranty</b>	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.



# PRESSALIT®

<b>Product</b>	PLUS shower seat 310, fixed height
<b>Item number</b>	R7310000
<b>Cleaning</b>	<p>PLUS shower seat.</p> <p>The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.</p> <p>Important: Polyurethane surfaces of PLUS shower seats and PLUS backrests contains an antibacterial surface, which will be compromised if cleaned with anything other than soap and water.</p> <p>The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.</p> <p><b>DECALCIFICATION OF ALUMINUM PARTS:</b></p> <p>Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts must be wiped over with a damp cloth wrung out in clear water.</p>

[pressalit.com](http://pressalit.com)

## PRESSALIT®