

# PRESSALIT.

Product	PLUS shower seat 450 with aperture, manually height adjustable		
Item number	R7431182000		
Colour	White		
Product description	LUS shower seat 450 with aperture, with back- and armrests. Manually height djustable by 195 mm. Armrests are independently height adjustable. The seat and e armrests are foldable. Pale grey cover plate for vertical wall track. aterials: Comfortable polyurethane foam over a plywood core, fitted to an aluminium rofile. The non-slip gripping surface of the armrests are made of soft SEBS corporating a glass-reinforced nylon core.		
	PLUS shower seat 450 with aperture, with back- and armrests. Manually height adjustable by 195 mm. Armrests are independently height adjustable. The seat and the armrests are foldable. Pale grey cover plate for vertical wall track. Materials: Comfortable polyurethane foam over a plywood core, fitted to an aluminium profile. The non-slip gripping surface of the armrests are made of soft SEBS incorporating a glass-reinforced nylon core. Excl. mounting kit.		
Adjustability	Height adjustable		
Adjustment height	175 mm		
Product capacity	Maximum user mass (seat): 200 kg. Maximum load for armrests is 55 kg. When the seat is loaded with 200 kg, each wall fastener is loaded with 24 kg.  The seat has been tested statically with safety factor 1.5, which is a requirement according to the applied assistive products standards.		



# PRESSALIT.

Product	PLUS shower seat 450 with aperture, manually height adjustable		
Item number	R7431182000		
Materials	The shower seat is made of polyurethane (PU) foam with a plywood core and this is covered with an in-mould coated surface that is protected using a clear PU lacquer. The backrest is made of polyurethane (PU) foam protected using a clear PU lacquer. The arms are primarily constructed of 10-micrometre anodized aluminium, with a number slip gripping surface at the end made of soft SEBS and inforporating a glass-reinforced nylon core. The hinge arm is also made of soft SEBS. Internal compone and fasteners are primarily made of stainless steel. The hinge barrel is capped with ABS.		
Ergonomy	Ergonomically designed seat - contact surface are 450 x 437 mm. Soft and slip-resistant material that has a warm feel. The oval shape of the armrests gives an earnd comfortable surface to lean on and push against.		
Features	The seat, backrest and armrests can be adjusted simultaneously thanks to a safe ar easy click system. The armrests can also be adjusted independently of the seat and backrest. The seat and armrests can fold up when not in use or to maximise floor space.		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.		
Cleaning	PLUS shower seat. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.		
	Important: Polyurethane surfaces of PLUS shower seats and PLUS backrests contains an antibacterial surface, which will be compromised if cleaned with anythin other than soap and water.		
	The product must be wiped down with a soft rag wrung out in clear water immediat after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.		
	DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts be wiped over with a damp cloth wrung out in clear water.		



## PRESSALIT.

Product				
Item number				

PLUS shower seat 450 with aperture, manually height adjustable

R7431182000


### Installation in different wall types


	3

#### Concrete >B25

V8612 - Mounting kit, 10 coach screws  $\emptyset$ 8 x 70, plugs SX10.

To be ordered separately.







#### Solid Brick >= Mz12

V8612 - Mounting kit, 10 coach screws  $\emptyset$ 8 x 70, plugs SX10.

To be ordered separately.






#### Solid Sand Lime Brick >= Hlz12

V8612 - Mounting kit, 10 coach screws  $\emptyset$ 8 x 70, plugs SX10.

To be ordered separately.







#### **Aerated Concrete P4**

V8662 - Mounting kit, 10 countersunk bolts M8 x 35, plugs FTP M 8.

To be ordered separately.






## Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8612 - Mounting kit, 10 coach screws Ø8 x 70, plugs SX10

NB! Plugs are not needed. To be ordered separately.





## PRESSALIT®

Product Item number	PLUS shower seat 450 with aperture, manually height adjustable R7431182000			
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood  Wall fasteners (10 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.			
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)  Wall fasteners (10 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.			
	Drywall (2 x 12,5 mm) water-resistant  Wall fasteners (10 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.			

pressalit.com